



STORED PRESSURE DRY CHEMICAL

6 YEAR WARRANTY

SIZES 2.5 LB. (1.14 KG.) TO 30 LB. (13.6 KG.)

TYPES:

- ABC – Multipurpose (ammonium phosphate) Powder
- PKD – Purple K (potassium bicarbonate) Powder
- PDC – Standard (sodium bicarbonate) Powder

FEATURES:

- Squeeze grip operation.
- Positive On/Off operation.
- Heavy duty steel cylinders.
- Pull pin safety locks.
- Glossy corrosion resistant red polyester powder paint finish.
- Water proof stainless steel gauge.
- Anodized aluminum valve.
- Units complete with wall brackets.
- Easy service valve construction –
 1. Remove valve and pick up tube.
 2. Remove spring and valve stem.
 3. Clean, Fill and reassemble.



OPTIONS:

- Corrosion control Primer Coatings can be applied for marine or offshore applications.
- 2-1/2 and 5 lb. vehicle brackets available.
- 10 lb. to 30 lb. units are available with heavy duty running board brackets, primed and painted for years of trouble free service in outside environments.

U.S.C.G. Approved and Underwriters Laboratories Inc. UL for

CLASS **A** - **B** - **C** FIRES

SPECIFICATIONS

PART NO.	MODEL	UL RATING	RANGE	CAPACITY	DISC. TIME	DIA.	WIDTH	HEIGHT
551900	ABC-025V	1A, 10-B.C.	8' - 10'	2 1/2 lbs.	8 - 10 sec.	3"	4.5"	16"
551904	ABC-025W	1-A, 10-B.C.	8' - 10'	2 1/2 lbs.	8 - 10 sec.	3"	4.5"	16"
551912	ABC-050V	3-A, 40-B.C.	10' - 15'	5 lbs.	13 - 15 sec.	4.25"	5.5"	17.8"
551907	ABC-050HW	3-A, 40-B.C.	10' - 15'	5 lbs.	13 - 15 sec.	4.25"	5.5"	17.8"
551910	ABC-050HWCR	3-A, 40-B.C.	10' - 15'	5 lbs.	13-15 sec.	4.25"	5.5"	17.8"
551918	ABC-10H	4-A, 80-B.C.	10' - 15'	10 lbs.	20 - 22 sec.	5.5"	9"	20"
551919	ABC-10CR	4-A, 80-B.C.	10' - 15'	10 lbs.	20 - 22 sec.	5.5"	9"	20"
551922	ABC-20G	20-A,120-B.C.	12' - 18'	20 lbs.	26 - 30 sec.	7"	10"	24"
551924	ABC-30G	20-A,120-B.C.	12' - 18'	27 lbs.	26 - 30 sec.	7"	10"	28"
551917	PKD-050V	30-B.C.	10' - 15'	5 lbs.	11 - 14 sec.	4.25"	5.5"	17.8"
551921	PKD-10G	80-B.C.	10' - 15'	10 lbs.	20 - 22 sec.	5.5"	9"	20"
551923	PKD-20G	120-B.C.	12' - 18'	20 lbs.	26 - 30 sec.	7"	10"	24"
551926	PKD-30G	160-B.C.	12' - 18'	28 lbs.	31 - 34 sec.	7"	10"	28"
551916	PDC-060HW	40-B.C.	10' - 15'	6 lbs.	13 - 15 sec.	4.25"	5.5"	17.8"
551920	PDC-10G	60-B.C.	10' - 15'	10 lbs.	17 - 20 sec.	5.5"	9"	20"
551964	PDC-20G	120-B.C.	12' - 18'	20 lbs.	26 - 30 sec.	7"	10"	24"
551925	PDC-30G	120-B.C.	12' - 18'	30 lbs.	26 - 30 sec.	7"	10"	28"

